

六角穴付きボルト UNC


ANSI B 18.3
ISO 4762
DIN 912



特徴

六角穴付きボルトのユニファイ規格(並目)用です。
キャップ UNCとも呼ばれます。

寸法図



寸法表

	ねじ山数	d2 MAX(mm)	d2 MIN(mm)	k MAX(mm)	k MIN(mm)	t MIN(mm)	六角穴サイズ*
#1	64	2.997	2.844	1.854	1.765	0.787	1/16
#2	56	3.556	3.403	2.184	2.108	0.965	5/64
#3	48	4.089	3.911	2.514	2.413	1.117	5/64
#4	40	4.648	4.47	2.844	2.743	1.295	3/32
#5	40	5.207	5.029	3.175	3.073	1.447	3/32
#6	32	5.74	5.537	3.505	3.403	1.625	7/64
#8	32	6.858	6.654	4.165	4.038	1.955	9/64
#10	24	7.924	7.696	4.826	4.699	2.286	5/32
#12	24	8.229	7.975	5.486	5.334	2.616	5/32
1/4	20	9.525	9.271	6.35	6.197	3.048	3/16
5/16	18	11.912	11.607	7.924	7.772	3.835	1/4
3/8	16	14.274	13.97	9.525	9.347	4.622	5/16
7/16	14	16.662	16.306	11.125	10.922	5.41	3/8
1/2	13	19.05	18.669	12.7	12.496	6.223	3/8
5/8	11	23.825	23.393	15.875	15.646	7.797	1/2
3/4	10	28.575	28.117	19.05	18.796	9.398	5/8
7/8	9	33.324	32.842	22.225	21.963	10.972	3/4
1"	8	38.1	37.566	25.4	25.095	12.573	3/4
1-1/4	7	47.625	47.04	31.75	31.394	15.748	7/8
1-1/2	6	57.15	56.489	38.1	37.719	18.923	1"