

C形止め輪軸用/Jタイプ セット

DIN 471/472

No Image

画像準備中

特徴

C形止め輪軸用(DIN471)と、Jタイプ(DIN472)のセットボックスです。

セット内容

1290363							
DIN471				DIN472			
サイズ	入数	サイズ	入数	サイズ	入数	サイズ	入数
6	25	20	15	14	18	28	15
8	22	22	15	15	18	30	15
10	18	24	15	16	18	32	15
11	18	25	15	18	18	35	12
12	18	28	12	20	18	36	12
14	18	30	12	22	18	38	12
15	18	32	12	24	15	40	10
16	18	35	12	25	15	42	10
17	18	36	10	26	15	47	10
18	15	40	10	27	15		

寸法情報

DIN471								DIN472							
d1	d3	公差	d4	d2	m H13	FR / KN	s	d1	d3	公差	d4	d2	m H13	FR / KN	s
6	5.6	+0.04/-0.15	11.7	5.7/h10	0.8	1.45	0.7	14	15.1	+0.36/-0.1	6.2	14.6	1.1	4.5	1
8	7.4	+0.06/-0.18	14.7	7.6/h10	0.9	3	0.8	15	16.2	+0.36/-0.1	7.2	15.7	1.1	5	1
10	9.3	+0.10/-0.36	17	9.6/h10	1.1	4	1	16	17.3	+0.36/-0.1	8	16.8	1.1	5.5	1
11	10.2	+0.10/-0.36	18	10.5/h11	1.1	4.5	1	18	19.5	+0.42/-0.13	9.4	19	1.1	6.5	1
12	11	+0.10/-0.36	19	11.5/h11	1.1	5	1	20	21.5	+0.42/-0.13	11.2	21	1.1	7.2	1
14	12.9	+0.10/-0.36	21.4	13.4/h11	1.1	6.35	1	22	23.5	+0.42/-0.13	13.2	23	1.1	8	1
15	13.8	+0.10/-0.36	22.6	14.3/h11	1.1	6.9	1	24	25.9	+0.42/-0.21	14.8	25.2	1.3	13.9	1.2
16	14.7	+0.10/-0.36	23.8	15.2/h11	1.1	7.4	1	25	26.9	+0.42/-0.21	15.5	26.2	1.3	14.6	1.2
17	15.7	+0.10/-0.36	25	16.2/h11	1.1	8	1	26	27.9	+0.42/-0.21	16.1	27.2	1.3	13.85	1.2
18	16.5	+0.10/-0.36	26.2	17/h11	1.3	17	1.2	27	29.1	+0.5/-0.25	16.6	28.4	1.3	-	1.2
20	18.5	+0.13/-0.42	28.4	19/h11	1.3	17.1	1.2	28	30.1	+0.5/-0.25	17.9	29.4	1.3	13.3	1.2
22	20.5	+0.13/-0.42	30.8	21/h11	1.3	16.9	1.2	30	32.1	+0.5/-0.25	19.9	31.4	1.3	13.7	1.2
24	22.2	+0.21/-0.42	33.2	22.9/h12	1.3	16.1	1.2	32	34.4	+0.5/-0.25	20.6	33.7	1.3	13.8	1.2
25	23.2	+0.21/-0.42	34.2	23.9/h12	1.3	16.2	1.2	35	37.8	+0.5/-0.25	23.6	37	1.6	26.9	1.5
28	25.9	+0.21/-0.42	37.9	26.6/h12	1.6	32.1	1.5	36	38.8	+0.5/-0.25	24.6	38	1.6	26.4	1.5
30	27.9	+0.21/-0.42	40.5	28.6/h12	1.6	32.1	1.5	38	40.8	+0.5/-0.25	26.4	40	1.6	28.2	1.5
32	29.6	+0.21/-0.42	43	30.3/h12	1.6	31.2	1.5	40	43.5	+0.9/-0.39	27.8	42.5	1.85	44.6	1.75
35	32.2	+0.25/-0.5	46.8	33/h12	1.6	30.8	1.5	42	45.5	+0.9/-0.39	29.6	44.5	1.85	44.7	1.75
36	33.2	+0.25/-0.5	47.8	34/h12	1.85	49.4	1.75	47	50.5	+1.1/-0.46	33.5	49.5	1.85	43.5	1.75
40	36.5	+0.39/-0.9	52.6	37.5/h12	1.85	51	1.75								